

AFUMEX® GOLD | 0.6/1kV | CLASS 5

FIRESTOP FS110 FLEXIBLE MULTICORE



Cable description

Fire rated, flexible multicore LSOH cable suitable for installation wiring.

Application

- Power supply to essential equipment such as lighting, fans and lifts in the event of a fire in confined spaces.
- Classified (WS52W) meaning the scope of testing is designed to confirm performance when installed in a wiring system.
- Circuit integrity up to an extreme temperature of 1050 °C at the end of 2 hours.
- LSZH – Suitable for confined and high people density areas such as underground transport tunnels, airports and public buildings.

Approvals/Qualifications

NATA accredited facility Qualification (third party)
AS/NZS 5000.1.
AS/NZS 3013 WS52W

Behaviour in flame and fire

Fire performance rating: AS/NZS 3013 WS52W
AS/NZS 4507 CI-3
Flame propagation: IEC 60332-3 cat A
IEC 60332-1
Halogen free/Low smoke emission:
AS/NZS 4507

Temperature range

Maximum operating temperature: +110 °C
Minimum operating temperature: -25 °C

Flexibility

Minimum bending radius:
Installed cables: 10D
During installation: 12D

Resistance to

Fire: 2 hrs
Chemical exposure: Occasional
Mechanical impact: Moderate
Water exposure: Spray
Solar radiation and weather exposure: UV stabilised

Cable design

Conductor: Flexible plain annealed copper (class 5)
Fire barrier: Mica glass tape
Insulation: X-HF-110 (LSOH)
Colour: 2 cores: Red, black
3 cores: Red, white, blue
4 cores: Red, white, blue, black
5 cores and above: White with numbered cores
Sheath: Red, HFS-110-TP (LSOH)

Installation conditions

In free air
In duct
Internal wiring
External building

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.



Physical & electrical characteristics

FIRESTOP FS110 FLEXIBLE MULTICORE – STANDARD EARTH

Product code	Number of cores	Nominal conductor area mm ²	Approx. overall diameter mm	Approx. mass kg/100 m	AS/NZS 3013 WS Rating
103CEFFFS110RD	3C+E	10	21.6	60.3	WS52W
163CEFFFS110RD	3C+E	16	24.2	83.1	WS52W
253CEFFFS110RD	3C+E	25	27.5	113.9	WS52W
353CEFFFS110RD	3C+E	35	30.7	148.3	WS52W
503CEFFFS110RD	3C+E	50	35.2	206.1	WS52W
703CEFFFS110RD	3C+E	70	40.8	283.7	WS52W
104CEFFFS110RD	4C+E	10	23.5	80	WS52W
164CEFFFS110RD	4C+E	16	26.5	108	WS52W
254CEFFFS110RD	4C+E	25	30.9	151	WS52W
354CEFFFS110RD	4C+E	35	33.8	196	WS52W
504CEFFFS110RD	4C+E	50	40.1	275	WS52W
704CEFFFS110RD	4C+E	70	45.3	378	WS52W

All other core count constructions available on request.

FIRESTOP FS110 FLEXIBLE MULTICORE – SPECIAL SIZE EARTH

Product code	Number of cores	Nominal conductor area mm ²	Nominal earth area mm ²	Approx. overall diameter mm	Approx. mass kg/100 m	AS/NZS 3013 WS Rating	Resistance DC @ 20°C - phase/earth
104C10EFFFS110RD	4C+E	10	10	22.9	86.4	WS52W	1.91/1.91
164C10EFFFS110RD	4C+E	16	10	25.2	110	WS52W	1.21/1.91
254C10EFFFS110RD	4C+E	25	10	29.0	152.3	WS52W	0.78/1.91
354C16EFFFS110RD	4C+E	35	16	32.0	205.8	WS52W	0.554/1.21

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.



CLASS 5 | FS110 MULTICORE

Size	Resistance		Reactance at 50Hz (ohm/km)	Voltage drop (mV/A.m)	
	DC @ 20°C	AC @ 110°C		Three phase	Single phase
10	1.91	2.59	0.0810	4.48	5.17
16	1.21	1.64	0.0779	2.84	3.28
25	0.780	1.06	0.0783	1.84	2.12
35	0.554	0.750	0.0761	1.31	1.51
50	0.386	0.523	0.0754	0.917	1.06
70	0.272	0.369	0.0744	0.654	0.755
95	0.206	0.280	0.0729	0.504	0.582
120	0.161	0.219	0.0723	0.403	0.465
150	0.129	0.176	0.0728	0.334	0.386
185	0.106	0.146	0.0730	0.286	0.330
240	0.0801	0.111	0.0722	0.234	0.270
300	0.0641	0.0905	0.0718	0.204	0.236

CURRENT CARRYING CAPACITY* | CLASS 5 | FS110 MULTICORE

Nominal conductor area mm ²	Unenclosed		Enclosed		Nominal conductor area mm ²	Unenclosed		Enclosed	
	Spaced A	Touching surface A	Metallic wiring enclosure in air A	Underground duct one duct A		Spaced A	Touching surface A	Metallic wiring enclosure in air A	Underground duct one duct A
TWO CORE					THREE & FOUR CORE				
10	94	88	75	84	10	80	75	65	71
16	124	116	100	109	16	106	99	84	91
25	163	154	129	139	25	140	131	112	118
35	202	190	163	171	35	173	162	137	143
50	254	238	202	209	50	218	204	175	178
70	318	299	257	259	70	273	255	217	217
95	381	357	303	304	95	327	306	263	259
120	450	421	362	357	120	387	360	306	298
150	515	482	412	403	150	444	413	356	341
185	586	547	474	456	185	505	470	402	381
240	698	652	577	541	240	602	559	489	453
300	799	745	656	611	300	688	638	-	509

* Based on 110°C conductor temperature, 40°C ambient air temperature and where applicable, burial depth of 0.5 m, soil temperature of 25°C and soil thermal resistivity of 1.2°C.m/W. Refer to AS/NZS 3008.1.1:2017 for other installation conditions.

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

